


## Solid-State Relay



Type:	SSR 50 A
Part No.:	910 - 01 - 50
Supplier Designation:	RM1A48D50
Switching Performance:	No-voltage release
Rated Current at Ohmic Load:	50 A
Operational Voltage Range:	42 - 530 VACeff
Peak Off-state Voltage:	1200 V <sub>ss</sub>
Control Voltage:	4.5...32 VDC
Operational Status Indication:	LED
Temperature Range (Operation):	-20...+70 °C
Temperature Range (Storage):	-40...+100 °C

## Triac



Type:	Triac
Part No.:	924 - 20 - 00
Supplier Designation:	BTA 26 - 800
Rated Current at Ohmic Load:	25 A
Operational Voltage Range:	42 - 530 VACeff
Peak Off-state Voltage:	800 V <sub>ss</sub>
Frequency Range:	45...65 Hz
Temperature Range (Operation):	-20...+70 °C
Temperature Range (Storage):	-40...+100 °C

## Super-quick Fuses



Safety fuses with super-quick actuation characteristics.  
For protection of solid-state relays.

Type	FF 10 A	FF 16 A	FF 20 A	FF 25 A	FF 30 A
Part No.	910 - 04 - 10	910 - 04 - 16	910 - 05 - 20	910 - 05 - 25	910 - 05 - 30
D / mm	6,3	6,3	10	10	10
L / mm	32	32	38	38	38

## Fuse Holders



910 - 50 - 10/ 5 x 20 mm  
910 - 50 - 11/ 6,3 x 32 mm




910 - 50 - 20  
10 x 38 mm



Fuse Holder, for JETmulti  
910 - 51 - 30



Cap 5 x 20 mm, for JETmulti  
910 - 51 - 31



Cap 6,3 x 32 mm, for JETmulti  
910 - 51 - 32



Cap 6,3 x 32 mm, for fitron  
910 - 51 - 42


## Interface Converters



### USB to RS 485 Converter

Part No. 960-20-10

Incl. 9-pin D-Sub device lead cable, 5 m long



### USB to RS 232 Converter


Part No. 960-20-20

Incl. 9-pin D-Sub device lead cable, 1.5 m long

## PC Connection Cables



Part No. 690-09-05 – 9-pin D-Sub, 5 m long



Part No. 690-09-06 – 9-pin D-Sub, 5 m long,  
A-B contacts with wire end ferrules and labels

## Equipment Trolley

Part No. 700 - 00 - 01

The trolley consists of a chrome-plated frame and two plastic-covered metal transportation surfaces, on four rollers.

### Technical Specifications:

Weight: Approx. 22 kg  
Load Capacity: Approx. 120 kg  
Wheels: Ø 100 mm, 20 mm wide  
2 steering & 2 fixed rollers  
Dimensions (L x W x H): 790 x 480 x 850 mm  
Usable Surface Area (L x W): 620 x 480 mm  
Daylight between Surfaces: 500 mm



**fiege**  
**electronic** GmbH

Fiege electronic GmbH  
Olbrichstraße 19/2  
D-69469 Weinheim  
Phone: +49 6201 259 58-0  
Fax: +49 6201 259 58-29  
info@fiege-electronic.de  
www.fiege-electronic.de